

LUC-463/Barclay 12-10-6-9

CLAIM AMENDMENTS

1 1. (Currently amended) An apparatus, comprising:
2 a network component that employs one or more call characteristics to make a
3 determination to initiate a request for one or more positions of one or more mobile
4 stations;

5 wherein the network component receives, in response to the request, the one or
6 more positions of the one or more mobile stations from a position component; and

7 wherein the position component determines the one or more positions of the one
8 or more mobile stations continuously.

1 2. (Original) The apparatus of claim 1, wherein the network component
2 performs a comparison of the one or more call characteristics with one or more
3 thresholds to make the determination to initiate the request for the one or more
4 positions of the one or more mobile stations.

1 3. (Currently amended) The apparatus of claim 2, wherein the one or more
2 call characteristics comprise a pilot signal strength characteristic, and wherein the one
3 or more thresholds comprise a pilot signal strength threshold, and wherein the network
4 component performs a comparison of the pilot signal strength characteristic with the
5 pilot signal strength threshold;

6 wherein the network component makes the determination to initiate the request
7 for the one or more positions of the one or more mobile stations based on a result of the
8 comparison of the pilot signal strength characteristic with the pilot signal strength
9 threshold.

LUC-463/Barclay 12-10-6-9

1 4. (Original) The apparatus of claim 2, wherein the network component
2 employs the one or more call characteristics to create one or more call statistics,
3 wherein the one or more thresholds comprise one or more call characteristic thresholds
4 and one or more call statistic thresholds;

5 wherein the network component performs a comparison of the one or more call
6 statistics with the one or more call statistic thresholds;

7 wherein the network component employs a comparison of the one or more call
8 characteristics with the one or more call characteristic thresholds and the comparison of
9 the one or more call statistics with the one or more call statistic thresholds to make the
10 determination to initiate the request.

1 5. (Original) The apparatus of claim 2, wherein the network component
2 comprises an interface, wherein the network component receives the one or more
3 thresholds from a service provider through employment of the interface.

1 6. (Original) The apparatus of claim 1, wherein the network component
2 employs the determination to initiate the request to promote an avoidance of congestion
3 in one or more cellular network communication paths.

1 7. (Currently amended) The apparatus of claim 6, wherein the network
2 component makes the determination to initiate the request upon an exceedance of the
3 one or more call characteristics relative to one or more thresholds;

4 wherein upon the exceedance of the one or more call characteristics relative to
5 the one or more thresholds, the network component and [[a]] the position component
6 cooperate to obtain the one or more positions of the one or more mobile stations.

LUC-463/Barclay 12-10-6-9

1 8. (Original) The apparatus of claim 7, wherein upon a termination of the
2 exceedance of the one or more call characteristics relative to the one or more
3 thresholds, the network component and the position component cooperate to
4 discontinue attainment of the one or more positions of the one or more mobile stations.

1 9. (Original) The apparatus of claim 1, wherein the network component
2 employs the one or more call characteristics to perform a selection of the one or more
3 mobile stations from a plurality of mobile stations;

4 wherein the network component employs the selection to formulate the request
5 for the one or more positions of the one or more mobile stations from the plurality of
6 mobile stations.

1 10. (Original) The apparatus of claim 1, wherein the one or more mobile
2 stations are associated with one or more cellular network cells;

3 wherein the network component employs the one or more call characteristics to
4 perform a selection of the one or more cellular network cells from a plurality of cellular
5 network cells;

6 wherein the network component employs the selection to formulate the request
7 for the one or more positions of the one or more mobile stations that are associated with
8 the one or more cellular network cells.

1 11. (Original) The apparatus of claim 10, wherein the network component
2 employs a switch component to identify the one or more mobile stations that are
3 associated with the one or more cellular network cells;

LUC-463/Barclay 12-10-6-9

4 wherein the network component employs the switch component to determine the
5 one or more positions of the one or more mobile stations that are associated with the
6 one or more cellular network cells.

1 12. (Original) The apparatus of claim 1, wherein the network component
2 receives the one or more positions of the one or more mobile stations in response to the
3 request;

4 wherein the network component employs the one or more positions of the one or
5 more mobile stations and the one or more call characteristics to develop a coverage
6 map.

1 13. (Original) The apparatus of claim 1, further comprising:

2 a switch component that provides the one or more call characteristics to the
3 network component;

4 wherein the network component employs the one or more call characteristics to
5 make a determination to initiate a request to the switch component;

6 wherein the switch component obtains the one or more positions of the one or
7 more mobile stations based on the request to the switch component.

1 14. (Original) The apparatus of claim 13, wherein the network component
2 provides to the switch component one or more call parameters;

3 wherein the switch component employs the one or more call parameters to
4 perform an identification of the one or more mobile stations from a plurality of mobile
5 stations;

LUC-463/Barclay 12-10-6-9

6 wherein the switch component employs the identification of the one or more
7 mobile stations from the plurality of mobile stations to obtain the one or more positions
8 of the one or more mobile stations.

1 15. (Original) The apparatus of claim 14, wherein the one or more mobile
2 stations are associated with one or more calls;

3 wherein the switch component employs the one or more call parameters to
4 perform an identification of the one or more calls from a plurality of calls;

5 wherein the switch component employs the identification of the one or more calls
6 from the plurality of calls to obtain the one or more positions of the one or more mobile
7 stations that are associated with the one or more calls.

1 16. (Currently amended) The apparatus of claim 13, wherein the network
2 component and the switch component receive the one or more positions of the one or
3 more mobile stations from ~~[[a]]~~ the position component;

4 wherein the network component and the switch component cooperate to develop
5 a coverage map through employment of the one or more positions of the one or more
6 mobile stations.

1 17. (Original) The apparatus of claim 16, wherein the position component
2 employs one or more of an Enhanced Forward Link Trilateration algorithm and an IS-
3 801 solution using an Assisted Global Positioning System (AGPS), Advanced Forward
4 Link Trilateration (AFLT) or combined AGPS/AFLT algorithm to determine the one or
5 more positions of the one or more mobile stations.

1 18. (Currently amended) A method, comprising the ~~step~~ steps of:

LUC-463/Barclay 12-10-6-9

2 initiating a request for one or more positions of one or more mobile stations
3 through employment of one or more call characteristics;

4 receiving, in response to the request, the one or more positions of the one or
5 more mobile stations; and

6 determining the one or more positions of the one or more mobile stations
7 continuously.

1 19. (Original) The method of claim 18, wherein the step of initiating the
2 request for the one or more positions of the one or more mobile stations through
3 employment of the one or more call characteristics comprises the steps of:

4 performing a comparison of the one or more call characteristics with one or more
5 thresholds; and

6 initiating the request for the one or more positions of the one or more mobile
7 stations based on the comparison.

1 20. (Original) The method of claim 19, wherein the step of initiating the
2 request for the one or more positions of the one or more mobile stations based on the
3 comparison comprises the steps of:

4 determining one or more call parameters associated with the one or more
5 thresholds;

6 identifying the one or more mobile stations from a plurality of mobile stations
7 through employment of the one or more call parameters; and

8 initiating the request for the one or more positions of the one or more mobile
9 stations through employment of the one or more call parameters.

LUC-463/Barclay 12-10-6-9

1 21. (Original) An article, comprising:
2 one or more computer-readable signal-bearing media;
3 means in the one or more media for initiating a request for one or more positions
4 of one or more mobile stations through employment of one or more call characteristics.

1 22. (New) The apparatus of claim 16, wherein the position component is pre-
2 provisioned with one or more intervals of time to determine the one or more positions of
3 the one or more mobile stations.

1